



Manifold Blocks

MAXPRO Custom Manifold Blocks can be provided in any configuration to suit customer needs, with fast delivery. Please contact Maxpro for a quotation.

MAXIMATOR Manifold Block Series allows reducing parts and potential leakages in high pressure piping systems.

Catalog Number	Pressure (psi) (psi @ R.T.)**	OD Tube in.	Orifice (in.)	Dimensions (in.)							Block Thickness
				A	B	C	D	E	F	G	
CUSTOMIZED MANIFOLD BLOCKS IN ANY CONFIGURATION FROM 10,000-152,000 PSI - CONTACT MAXPRO											
21MB64M	22,500	1/4	0.11	3.39	1.54	2.6	0.22	0.28	3.11	0.77	0.63
21MB66M	22,500	3/8	0.2	3.39	2.01	2.38	0.26	0.37	3.01	1.0	0.79
21MB69M	22,500	9/16	0.307	5.12	2.5	3.86	0.33	0.41	4.7	1.25	1.02
21MB612M	22,500	3/4	0.438	6.5	2.99	5.0	0.35	0.49	6.0	1.5	1.38
21MB616M	22,500	1	0.562	7.25	4.13	5.45	0.53	0.69	6.83	2.07	1.77
65MB64H	65,000	1/4	0.094	3.44	2.01	2.52	0.22	0.35	3.09	1.0	1.02
65MB66H	65,000	3/8	0.125	3.76	2.01	2.66	0.26	0.35	3.41	1.0	1.02
65MB69H	65,000	9/16	0.19	5.12	2.64	3.74	0.33	0.37	4.74	1.32	1.54
152MB65U	152,000	5/16	0.094	4.72	3.03	3.21	0.33	0.59	4.13	1.52	1.26

**See page 2 in the Technical Section for Pressure/Temperature Derating Chart.

