GAS RECEIVERS

Alloy Steel with nickel plating

1/4" high pressure inlet/oulet connections on each end. Optional 1/4" NPT connections available.

REC-36S....36 Cu. In. - 10,000 psi, 2.5" Dia. x 20.63" L overall
 REC-66S....66 Cu. In. - 10,000 psi, 2.5" Dia. x 33" L overall

DRY AIR SPOOLS

For severe duty service

- The Dry Air Spool (DAS) option should be considered for extreme operating conditions involving air or gas drive mediums below 0°F. dewpoint, or very cold climate applications (-40°C.).
- This option eliminates lubrication maintenance of the spool valve.





AIR RECEIVER TANKS Carbon Steel, ASME Certified

- T1-400......1 Gallon 400 psi, no mounting, 6" OD x 16" L,10 lbs., connections: (2) 3/4" FNPT (1) 1/4" FNPT
- **T4-600**......4 Gallon 600 psi, with mounting base, 10.75" Dia. x 13.75" H x 15" L, 46 lbs., connections: (2) 3/4" FNPT (3) 3/8" FNPT (2)1/4" FNPT
- **7-302461**...10 Gallon 200 psi, with mounting legs, 10" OD x 30" L. x 11.5" H, 43 lbs., connections: (2) 3/4"
- **T-302464**...15 Gallon 200 psi, with mounting legs, 12" OD x 33" L, 14.5" H, 51 lbs., connections: (2) 3/4" FNPT (3) 1/2" FNPT (1) 1/4" FNPT
- **T-302470**...30 Gallon 200 psi, with mounting legs, 16" OD x 38" L, 20.6" H, 111 lbs., connections: (2) 1 1/2" FNPT (3) 3/4" FNPT (1) 1/2" FNPT

AIR CONTROL PACKAGES

Consisting of a filter, regulator with gauge, shut-off valve and required fittings

- ACM....For all LC, PPO, PP & PPSF pumps, and MPLV air amplifiers
- AC.....For all S Pumps
- ACP.....For all L, LO & LSF pumps, DLA & GPLV air amplifiers and DLE gas boosters
- ACG....For all GX pumps



PUMP CYCLE COUNTERS

To order: add suffix to pump P/N, eg. PPO12-CCW

- **CCP**....Panel mount, 0 999,999 max. cycles, 1" high x 2" wide hole
- CCW...Wall mount, 0 999,999 max cycles
 Reset button



CLEANING FOR OXYGEN SERVICE

Meets or exceeds standards of: CGA G-4.1, ASTM G93, SAE ARP117

Call Maxpro Technologies to receive a quotation regarding cleaning for oxygen service.

